

Submersible Dredging Pumps | Remote Controlled Dredges Cable Dredgers | Amphibious Dredges





DRM Crawler multi-purpose dredge

The DRM dredge series are multi-purpose machines that can work both on water and on land.

Designed to tackle projects where site conditions vary from very shallow to deeper areas and in projects where extreme mobility is important.

The DRM design provides the mobility of an amphibious excavator together with the stability of a dredger without side poontons.

Main characteristics:

- Total mobility in both land and water
- System operated by a single operator
- Dredging depth up to 6.5m
- Capable of pumping up to 1000m3/h
- Possibility to use different hydraulic tool attachments
- Available with bucket up to 1,5 m³
- •Packed and shipped infive 40ft containers for quick installation





Special Features

1.Hydraulic Power Units

Dragflow's Hydraulic Power Units are custom built to handle the requirements of our machines.

They can include a wide range of features:

- Completely customisable for additional tools
- Available with Diesel engines or electric motors to run the hydraulic system
- Sound proof Enclosure for reduced noise levels during operation
- Diesel engines available in TIER 4 FINAL STAGE V

2. Undercarriage tracks

The DRM tracks can be made in either steel or polymeric material. Additionally, they are joined by individual links that allo an easier maintenance and replacement, making the entire machine much more reliable.

3.Flotation Studies

Flotation studies were performed according to IACS regulations to obtain the perfect setup for the machine under these extreme conditions.



Submersible Dredging Pumps | Remote Controlled Dredges Cable Dredgers | Amphibious Dredges

DRAGFLOW

DRM





Operator cabin

- · Complete control panel
- · Heating and air conditioning
- · Ergonomic seat
- · Safety equipment
- · Equipment status
- · Emergency stop controls

- 1	
4	\$

Length	11.5m
Width	7m
Height	4.5m
Weight	53 ton



Two (2)pontoons 11m x 2 m x 1.5 m with central floater

DRAFT 1.5 m



HY85/180	Max Capacity	[m³/h] 1000
	Max Head	[m] 60
	Discharge Diameter	DN200
	Max Solid Handling	90 m

Hydraulic Arm

- · Precisely moves pump up and down
- · Depth measuring sensors
- · Possibility to install other hydraulic tools

Hydraulic Pack

- Sound proof canopy
- · Diesel engine
- · Closed hydraulic circuit
- Oil pump
- · Completely customizable hydraulic circuits

Winches (x4)

- · For moving the dredge
- · Steel cables
- Optional propeller
- Stabilizer Spuds (x4)

Floaters

- Two pontoons 11x2x1,5m with central floater for exceptional stability
- · Small draft



HPU

 The hydraulic thruster is driven from the operator cabin and drives the dredge independently without any connection to the shore.



TRANSPORT

Transportable in five containers 40'. Assembly operations takes as short as 8-10 hours



Type.....Diesel engine (265 kW/360HP) Fuel Capacity......1200 L Emission Compliance......EU STAGE III A



Submersible Dredging Pumps | Remote Controlled Dredges Cable Dredgers | Amphibious Dredges



DRSP Multi-purpose dredge

DRSP (Multi-purpose dredge) represents a step over on approach of dredging technique. The extreme mobility in any kind of swamp,together with the full floatability, allows to reach the most the most remote locations otherwise impossible to get with any other equipment.

Pumping capacity up to 600-800 m3/h with delivery distance up to 1500 meters or more can make possible to perform works with the highest productivity ever. The combination of such equipment with the DRAGFLOW dredging technology makes the DRSP unbeatable in terms of efficiency and durability.



Main Features

- Great stability and buoyancy in different water environments
- Independent propulsion system in both water and on land
- Dredgeup to 6.5m of depth
- Interchangeable hydraulic tools



Submersible Dredging Pumps | Remote Controlled Dredges Cable Dredgers | Amphibious Dredges







Operator cabin

- · Complete control panel
- · Heating and air conditioning
- · Ergonomic seat
- · Safety equipment
- · Equipment status
- · Emergency stop controls



Length	10.5 m
Width	6.4 m
Height	3.4 m
Weight	53 ton

DIMENSIONS

One (1) main pontoon 10.5m x 3.30 2 m x 1.1 m with two (2) lateral pontoons 6.7 m x 1.5 x 1.1





Max Capacity.....[m3/h] 1000 Max Head.....[m] 60 Discharge Diameter.....DN200 Max Solid Handling......90 m

Main Arm

Max working depth 6,7m Precisely moves pump up and down Depth measuring sensors Possibility to install other hydraulic tools

Power Pack

The hydraulic power pack can be based on electric motors or on diesel engines in compliance with the latest European emission standards.

Rear Stabilizers

Thanks to a max working depth of 7m, the rear stabilizers can anchor the dredge during the dredging operations.

Front Stabilizers

The stabilizers increase the lateral stability of the dredge during the movement of the arm.

Service crane

With its max extension of 6m, it can be used for several operations on the dredge.



Thruster

The hydraulic thruster is driven from the operator cabin and drives the dredge independently without any connection to the shore.



With this upgrade, the DRSP dredges achieves an extra level of independence for those particularly harsh environments. The tracked module can be added to new and existing DRSP dredges for an extra mobility boost.



TRANSPORT Transportable in five containers 40'. Assembly operations takes as short as 8-10 hours



Type.....VECO Diesel engine (265 kW/360HP) other brands available on demand Fuel Capacity.....1200 L

Emission Compliance.....STAGE V or lower according to the legislation of the country of application





Submersible Dredging Pumps | Remote Controlled Dredges Cable Dredgers | Amphibious Dredges





DRAGFLOW DREDGING

HY85/160 Max Capacity......[m³/h] 1000 Max Head.....[m] 60 Discharge Diameter.....DN200 Max Solid Handling......90 m

Hydraulic Motor Motor Displacement:......[cc - (cu in)]: 160 - (9.8)

Materials

Casing Spheroidal cast iron EN-GJS-800-2 (EN 1563) Wear parts High chrome EN-GJN-HV600 (XCr18) (EN 12513)

ACCESSORIES



DTM Cutter Head

- Hydraulic motor Radial piston
- Capacity (I/min) 40

· Cap. Sae. 1000 lt

Double base in S355

Weight: 830 kg

• Tooth system materials: harder and tougher alloy steel

Backhoe Bucket without teeth 1000 It



Side Cutters

- · Replaceable teeth
- Radial piston hydraulic motor
- Oil requirement: 35 l/min each
- · Rotates in both directions



Backhoe Bucket 600 It

- N. 4 teeth type Cat J300
- Cap. Sae: 600 lt
- Weight: 580 kg
- Double base in S355



- Min Oil Flow: 100 l/min
- Working pressure: 150 bar
- Max centrifugal force: 12000 kg
- Vibration numbers: 2300
- Weight: 1200 kg



Bucket Rake

- N. 11 teeth type Cat J300
- Weight: 1200 kg

Clamshell Bucket 300 kg

Weight: 300 kg
Static flow: 2 ton
Force: 1,7 ton
Surface: 0,35 m²

• Distance between tips: 200 mm aprox





Call now 0800 482 747 info@primepump.co.nz primepump.co.nz

Amphibious Dredges Submersible Dredging Pumps | Remote Controlled Dredges Cable Dredgers | Amphibious Dredges







